



FABER CHIMICA S.R.L.

PPF56 - DEC 21

Revision n. 8.1  
Dated 29/10/2021  
Printed on 29/10/2021  
Page n. 1/18  
Replaced revision:8.0 (Dated: 13/10/2020)

## Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Code: PFP56  
Product name: DEC 21  
Chemical name and synonym: DEC 21

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: SOLVENT STRIPPER

#### 1.3. Details of the supplier of the safety data sheet

Name: FABER CHIMICA S.R.L.  
Full address: Via Ceresani 10  
District and Country: 60044 Campo D'Olmo - Fabriano (ANCONA)  
ITALIA  
Tel. 0732627178  
Fax 073222395

e-mail address of the competent person  
responsible for the Safety Data Sheet

quality@fabersurfacecare.com

#### 1.4. Emergency telephone number

For urgent inquiries refer to

Belgium  
Centre Antipoisons  
c/o Hôpital Militaire Reine Astrid, Rue Bruyn 1, 1120 Bruxelles, Belgium  
Phone+32022649636  
E-mail info@poisoncentre.be  
Croatia  
Croatian Institute of Public Health, Division for Toxicology  
Borongajska 83g, 10000 Zagreb, Croatia  
Phone+38514686910  
E-mail toksikologija@hzjz.hr  
Denmark  
Danish Environmental Protection Agency  
Haraldsgade 53, 2100 København Ø, Denmark  
Phone+45 72 54 40 00  
E-mail mst@mst.dk  
Estonia  
Health Board  
Paldiski road 81,10617 Tallinn, Estonia  
Phone+372 794 3500  
E-mail clp @ terviseamet.ee, info @ terviseamet.ee  
Iceland  
Poisons Information Center - Icelandic University Hospital  
Fossvogur, Reykjavík, Iceland  
Phone+354 543 22 22  
E-mail eitur@landspitali.is  
Ireland  
National Poisons Information Centre  
Beaumont Hospital, Beaumont, Dublin 9., Ireland  
E-mail chemicalsinfo @ beaumont.ie  
Latvia



FABER CHIMICA S.R.L.

PPF56 - DEC 21

Revision n. 8.1  
Dated 29/10/2021  
Printed on 29/10/2021  
Page n. 2/18  
Replaced revision:8.0 (Dated: 13/10/2020)

**State Ltd "Latvian Environment, Geology and Meteorology Centre"**

Maskavas Street 165, Riga, LV-1019, Latvia

Phone +371 67032600

E-mail lvgmc@lvgmc.lv

Lithuania

**Environmental Protection Agency**

Juozapavicius st. 9, LT-09311 Vilnius, Lithuania

Phone +370 70662008

E-mail aaa@aaa.am.lt

Malta

**Malta Competition and Consumer Affairs Authority (MCCAA)**

Mizzi House, National Road, Blata I-Bajda HMR9010, Malta

Phone +356 2395 2000

E-mail info@mccaa.org.mt

Norway

**Norwegian Environment Agency**

Postboks 5672 Torgarden, 7485 Trondheim, Norway

Phone+4573580500

E-mail produktregisteret@miljodir.no

Portugal

**Centro de informação antivenenos**

Rua Almirante Barroso, 36 1000-013 Lisboa, Portugal

Phone +351213303271

E-mail ciav.tox@inem.pt

Sweden

**Swedish Poisons Information Centre**

Giftinformationscentralen 171 76 Stockholm, Sweden

Phone +46104566750

E-mail giftinformation@gic.se

## SECTION 2. Hazards identification

### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 2	H225	Highly flammable liquid and vapour.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.

### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:





FABER CHIMICA S.R.L.

PPF56 - DEC 21

Revision n. 8.1  
Dated 29/10/2021  
Printed on 29/10/2021  
Page n. 3/18  
Replaced revision:8.0 (Dated: 13/10/2020)

Signal words: Danger

Hazard statements:

**H225** Highly flammable liquid and vapour.  
**H304** May be fatal if swallowed and enters airways.  
**H319** Causes serious eye irritation.  
**H315** Causes skin irritation.  
**H336** May cause drowsiness or dizziness.

Precautionary statements:

**P210** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
**P331** Do NOT induce vomiting.  
**P280** Wear protective gloves/ protective clothing / eye protection / face protection.  
**P301+P310** IF SWALLOWED: Immediately call a POISON CENTER / doctor  
**P370+P378** In case of fire: use carbon dioxide, foam, chemical powder to extinguish.  
**P261** Avoid breathing dust / fume / gas / mist / vapours / spray.

**Contains:** Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics  
Methyl acetate  
2-butoxyethanol

### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration  $\geq$  0.1%.

## SECTION 3. Composition/information on ingredients

### 3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
<b>Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, &lt;2% aromatics</b> CAS 64742-48-9 EC 919-857-5 INDEX REACH Reg. 01-2119463258-33	$70 \leq x < 74$	Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066
<b>2-BUTOXYETHANOL</b> CAS 111-76-2 EC 203-905-0 INDEX 603-014-00-0	$16,5 \leq x < 18$	Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, Eye Irrit. 2 H319, Skin Irrit. 2 H315 LD50 Oral: 1200 mg/kg, STA Dermal: 1100 mg/kg, STA Inhalation vapours: 11 mg/l
<b>METHYL ACETATE</b> CAS 79-20-9 EC 201-185-2	$8 \leq x < 9$	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066



FABER CHIMICA S.R.L.

PPF56 - DEC 21

Revision n. 8.1  
Dated 29/10/2021  
Printed on 29/10/2021  
Page n. 4/18  
Replaced revision:8.0 (Dated: 13/10/2020)

INDEX 607-021-00-X

**METHANOL**

CAS 67-56-1

1,5 ≤ x < 2

Flam. Liq. 2 H225, Acute Tox. 3 H301, Acute Tox. 3 H311, Acute Tox. 3 H331, STOT SE 1 H370  
STOT SE 2 H371: ≥ 3%

EC 200-659-6

INDEX 603-001-00-X

STA Oral: 100 mg/kg, STA Dermal: 300 mg/kg, STA Inhalation gas: 700 ppm,  
STA Inhalation mists/powders: 0,501 mg/l, STA Inhalation vapours: 3 mg/l

**TOLUENE**

CAS 108-88-3

0,6 ≤ x < 0,7

Flam. Liq. 2 H225, Repr. 2 H361d, Asp. Tox. 1 H304, STOT RE 2 H373, Skin Irrit. 2 H315, STOT SE 3 H336

EC 203-625-9

INDEX 601-021-00-3

The full wording of hazard (H) phrases is given in section 16 of the sheet.

## SECTION 4. First aid measures

### 4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

## SECTION 5. Firefighting measures

### 5.1. Extinguishing media

**SUITABLE EXTINGUISHING EQUIPMENT**

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

**UNSUITABLE EXTINGUISHING EQUIPMENT**

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

### 5.2. Special hazards arising from the substance or mixture

**HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

### 5.3. Advice for firefighters

**GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for



FABER CHIMICA S.R.L.

PPF56 - DEC 21

Revision n. 8.1  
Dated 29/10/2021  
Printed on 29/10/2021  
Page n. 5/18  
Replaced revision:8.0 (Dated: 13/10/2020)

extinction and the remains of the fire according to applicable regulations.

#### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## SECTION 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

## SECTION 7. Handling and storage

### 7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

### 7.3. Specific end use(s)

Information not available

## SECTION 8. Exposure controls/personal protection

**8.1. Control parameters**

## Regulatory References:

DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
ESP	España	Límites de exposición profesional para agentes químicos en España 2021
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	TLV-ACGIH RCP TLV	ACGIH 2020 ACGIH TLVs and BEIs – Appendix H

**TOLUENE****Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	190	50	760	200	SKIN
MAK	DEU	190	50	760	200	SKIN
VLA	ESP	192	50	384	100	SKIN
VLEP	FRA	76,8	20	384	100	SKIN
VLEP	ITA	192	50			SKIN
TGG	NLD	150		384		
WEL	GBR	191	50	384	100	SKIN
OEL	EU	192	50	384	100	SKIN
TLV-ACGIH		75,4	20			

**METHANOL****Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	270	200	1080	800	SKIN
MAK	DEU	130	100	260	200	SKIN
VLA	ESP	266	200			SKIN
VLEP	FRA	260	200	1300	1000	SKIN 11
VLEP	ITA	260	200			SKIN
TGG	NLD	133				SKIN
WEL	GBR	266	200	333	250	SKIN
OEL	EU	260	200			
TLV-ACGIH		262	200	328	250	SKIN

**METHYL ACETATE****Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	620	200	1240 (C)	400 (C)	
MAK	DEU	310	100	1240	400	



**FABER CHIMICA S.R.L.**

**PPF56 - DEC 21**

Revision n. 8.1  
Dated 29/10/2021  
Printed on 29/10/2021  
Page n. 7/18  
Replaced revision:8.0 (Dated: 13/10/2020)

VLA	ESP	616	200	770	250	
VLEP	FRA	610	200	760	250	SKIN
TGG	NLD	100				
WEL	GBR	616	200	770	250	
TLV-ACGIH		606	200	757	250	

**2-BUTOXYETHANOL**  
**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	49	10	98 (C)	20 (C)	SKIN
MAK	DEU	49	10	98	20	SKIN Hinweis
VLA	ESP	98	20	245	50	SKIN
VLEP	FRA	49	10	246	50	SKIN
VLEP	ITA	98	20	246	50	SKIN
TGG	NLD	100		246		SKIN
WEL	GBR	123	25	246	50	SKIN
OEL	EU	98	20	246	50	SKIN
TLV-ACGIH		97	20			

Predicted no-effect concentration - PNEC			
Normal value in fresh water		8,8	mg/l
Normal value in marine water		0,88	mg/l
Normal value for fresh water sediment		8,14	mg/kg
Normal value for marine water sediment		2,8	mg/kg

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation	123 mg/m3	VND	426 mg/kg	49 mg/m3	246 mg/m3	VND	663 mg/m3	98 mg/m3
Skin	VND	VND	44.5 mg/kg/d	89 mg/kg/d	VND	VND	38 mg/kg bw/d	75 mg/kg/d

**Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics**  
**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
RCP TLV		1200	197			

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

**8.2. Exposure controls**

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.



FABER CHIMICA S.R.L.

PPF56 - DEC 21

Revision n. 8.1  
Dated 29/10/2021  
Printed on 29/10/2021  
Page n. 8/18  
Replaced revision:8.0 (Dated: 13/10/2020)

When choosing personal protective equipment, ask your chemical substance supplier for advice.  
Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

#### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

#### SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

#### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

#### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a type AX filter, whose limit of use will be defined by the manufacturer (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

#### ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

## SECTION 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	colourless	
Odour	characteristic of solvent	
Odour threshold	1/100	
Melting point / freezing point	Not available	
Initial boiling point	Not available	
Flammability	flammable liquid	
Lower explosive limit	1,7	
Upper explosive limit	7,6	
Flash point	< 21 °C	
Auto-ignition temperature	Not available	
Decomposition temperature	Not available	
pH	Not applicable	
Kinematic viscosity	Not available	





Solubility	insoluble in water	
Partition coefficient: n-octanol/water	2,3	Temperature: 25 °C
Vapour pressure	Not available	
Density and/or relative density	0,805 g/cm <sup>3</sup>	Temperature: 20 °C
Relative vapour density	Not available	
Particle characteristics	Not applicable	

**9.2. Other information**

9.2.1. Information with regard to physical hazard classes  
Information not available

9.2.2. Other safety characteristics

Information not available

**SECTION 10. Stability and reactivity****10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

TOLUENE

Avoid exposure to: light.

2-BUTOXYETHANOL

Decomposes under the effect of heat.

**10.2. Chemical stability**

The product is stable in normal conditions of use and storage.

**10.3. Possibility of hazardous reactions**

The vapours may also form explosive mixtures with the air.

TOLUENE

Risk of explosion on contact with: fuming sulphuric acid,nitric acid,silver perchlorate,nitrogen dioxide,non-metal halogenates,acetic acid,organic nitrocompounds.May form explosive mixtures with: air.May react dangerously with: strong oxidising agents,strong acids,sulphur.

2-BUTOXYETHANOL

May react dangerously with: aluminium,oxidising agents.Forms peroxides with: air.

**10.4. Conditions to avoid**

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

2-BUTOXYETHANOL



Avoid exposure to: sources of heat,naked flames.

#### 10.5. Incompatible materials

Information not available

#### 10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

2-BUTOXYETHANOL

May develop: hydrogen.

## SECTION 11. Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Metabolism, toxicokinetics, mechanism of action and other information

Information not available

#### Information on likely routes of exposure

TOLUENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air; contact with the skin of products containing the substance.

METHANOL

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

TOLUENE

Toxic effect on the central and peripheral nervous system with encephalopathy and polyneuritis; irritating for the skin, conjunctiva, cornea and respiratory apparatus.

METHANOL

The minimum lethal dose for humans by ingestion is considered to be in the range from 300 to 1000 mg/kg. Ingestion of 4-10 ml of the substance may cause permanent blindness in adult humans (IPCS).

Interactive effects**TOLUENE**

Certain drugs and other industrial products can interfere with the metabolism of the toluene.

ACUTE TOXICITY

ATE (Inhalation - mists / powders) of the mixture:	> 5 mg/l
ATE (Inhalation - vapours) of the mixture:	> 20 mg/l
ATE (Inhalation - gas) of the mixture:	> 20000 mg/l
ATE (Oral) of the mixture:	>2000 mg/kg
ATE (Dermal) of the mixture:	>2000 mg/kg

**TOLUENE**

LD50 (Oral):	5580 mg/kg Rat
LD50 (Dermal):	12124 mg/kg Rabbit
LC50 (Inhalation vapours):	28,1 mg/l/4h Rat

**METHANOL**

STA (Oral):	100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
STA (Dermal):	300 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
STA (Inhalation mists/powders):	0,501 mg/l estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
STA (Inhalation vapours):	3 mg/l estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
STA (Inhalation gas):	700 ppm estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)

**2-BUTOXYETHANOL**

LD50 (Oral):	1200 mg/kg Guinea pig
LC50 (Inhalation vapours):	2,2 mg/l/4h Rat
STA (Inhalation vapours):	11 mg/l estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)

**Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics**

LD50 (Oral):	> 5000 mg/kg rat
LD50 (Dermal):	> 5000 mg/kg rabbits
LC50 (Inhalation vapours):	> 5000 mg/m3

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION



FABER CHIMICA S.R.L.

PPF56 - DEC 21

Revision n. 8.1  
Dated 29/10/2021  
Printed on 29/10/2021  
Page n. 12/18  
Replaced revision:8.0 (Dated: 13/10/2020)

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

TOLUENE

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 1999).  
The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Toxic for aspiration

**11.2. Information on other hazards**



Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

## SECTION 12. Ecological information

### 12.1. Toxicity

Hydrocarbons, C9-C11, n-alkanes,  
isoalkanes, cyclics, <2% aromatics  
EC50 - for Crustacea 1000 mg/l/48h

### 12.2. Persistence and degradability

TOLUENE  
Solubility in water 100 - 1000 mg/l  
Rapidly degradable

METHANOL  
Solubility in water 1000 - 10000 mg/l  
Rapidly degradable

METHYL ACETATE  
Solubility in water 243500 mg/l  
Rapidly degradable

2-BUTOXYETHANOL  
Solubility in water 1000 - 10000 mg/l  
Rapidly degradable

### 12.3. Bioaccumulative potential

TOLUENE  
Partition coefficient: n-octanol/water 2,73  
BCF 90

METHANOL  
Partition coefficient: n-octanol/water -0,77  
BCF 0,2

METHYL ACETATE  
Partition coefficient: n-octanol/water 0,18

2-BUTOXYETHANOL  
Partition coefficient: n-octanol/water 0,81

### 12.4. Mobility in soil



FABER CHIMICA S.R.L.

PFP56 - DEC 21

Revision n. 8.1  
Dated 29/10/2021  
Printed on 29/10/2021  
Page n. 14/18  
Replaced revision:8.0 (Dated: 13/10/2020)

METHYL ACETATE

Partition coefficient: soil/water 0,18

#### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

#### 12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

#### 12.7. Other adverse effects

Information not available

### SECTION 13. Disposal considerations

#### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

#### CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

### SECTION 14. Transport information

#### 14.1. UN number or ID number

ADR / RID, IMDG, 1263  
IATA:

#### 14.2. UN proper shipping name

ADR / RID: PAINT or PAINT RELATED MATERIAL

IMDG: PAINT or PAINT RELATED MATERIAL

IATA: PAINT or PAINT RELATED MATERIAL

#### 14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3

IMDG: Class: 3 Label: 3





FABER CHIMICA S.R.L.

PPF56 - DEC 21

Revision n. 8.1  
Dated 29/10/2021  
Printed on 29/10/2021  
Page n. 15/18  
Replaced revision:8.0 (Dated: 13/10/2020)

IATA: Class: 3 Label: 3



#### 14.4. Packing group

ADR / RID, IMDG, II  
IATA:

#### 14.5. Environmental hazards

ADR / RID: NO  
IMDG: NO  
IATA: NO

#### 14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 33	Limited Quantities: 5 L	Tunnel restriction code: (D/E)
	Special provision: 640D		
IMDG:	EMS: F-E, <u>S-E</u>	Limited Quantities: 5 L	
IATA:	Cargo:	Maximum quantity: 60 L	Packaging instructions: 364
	Pass.:	Maximum quantity: 5 L	Packaging instructions: 353
	Special provision:	A3, A72, A192	

#### 14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

## SECTION 15. Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

#### Product

Point 40

#### Contained substance

Point 75

Point 69 METHANOL



FABER CHIMICA S.R.L.

PPF56 - DEC 21

Revision n. 8.1  
Dated 29/10/2021  
Printed on 29/10/2021  
Page n. 16/18  
Replaced revision:8.0 (Dated: 13/10/2020)

Point 48 TOLUENE

Regulation (EC) No. 2019/1148 - on the marketing and use of explosives precursors

Not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage  $\geq$  than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

### 15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

## SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Repr. 2	Reproductive toxicity, category 2
Acute Tox. 3	Acute toxicity, category 3
STOT SE 1	Specific target organ toxicity - single exposure, category 1
Acute Tox. 4	Acute toxicity, category 4
Asp. Tox. 1	Aspiration hazard, category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3





<b>H225</b>	Highly flammable liquid and vapour.
<b>H226</b>	Flammable liquid and vapour.
<b>H361d</b>	Suspected of damaging the unborn child.
<b>H301</b>	Toxic if swallowed.
<b>H311</b>	Toxic in contact with skin.
<b>H331</b>	Toxic if inhaled.
<b>H370</b>	Causes damage to organs.
<b>H302</b>	Harmful if swallowed.
<b>H312</b>	Harmful in contact with skin.
<b>H332</b>	Harmful if inhaled.
<b>H304</b>	May be fatal if swallowed and enters airways.
<b>H373</b>	May cause damage to organs through prolonged or repeated exposure.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H336</b>	May cause drowsiness or dizziness.
<b>EUH066</b>	Repeated exposure may cause skin dryness or cracking.

**LEGEND:**

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

**GENERAL BIBLIOGRAPHY**

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament



**FABER CHIMICA S.R.L.**

**PPF56 - DEC 21**

Revision n. 8.1  
Dated 29/10/2021  
Printed on 29/10/2021  
Page n. 18/18  
Replaced revision:8.0 (Dated: 13/10/2020)

8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
  9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
  10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
  11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
  12. Regulation (EU) 2016/1179 (IX Atp. CLP)
  13. Regulation (EU) 2017/776 (X Atp. CLP)
  14. Regulation (EU) 2018/669 (XI Atp. CLP)
  15. Regulation (EU) 2019/521 (XII Atp. CLP)
  16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
  17. Regulation (EU) 2019/1148
  18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
  19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
  20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
  21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- The Merck Index. - 10th Edition
  - Handling Chemical Safety
  - INRS - Fiche Toxicologique (toxicological sheet)
  - Patty - Industrial Hygiene and Toxicology
  - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
  - IFA GESTIS website
  - ECHA website
  - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

**CALCULATION METHODS FOR CLASSIFICATION**

**Chemical and physical hazards:** Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

**Health hazards:** Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

**Environmental hazards:** Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

**Changes to previous review:**

MSDS update for software use