



**FABER CHIMICA S.R.L.**  
**PPF12 - DEEP ENHANCER**

Revision n. 10.1  
Dated 04/03/2022  
Printed on 04/03/2022  
Page n. 1/16  
Replaced revision:10.0 (Dated: 13/10/2021)

## Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Code: PFP12  
Product name: DEEP ENHANCER  
Chemical name and synonym: DEEP ENHANCER

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: IMPREGNATING COLOUR ENHANCING TREATMENT FOR LOW ABSORBING MATERIALS

#### 1.3. Details of the supplier of the safety data sheet

Name: FABER CHIMICA S.R.L.  
Full address: Via Ceresani 10  
District and Country: 60044 Campo D'Olmo - Fabriano (ANCONA)  
ITALIA  
Tel. 0732627178  
Fax 073222395

e-mail address of the competent person  
responsible for the Safety Data Sheet

[quality@fabersurfacecare.com](mailto:quality@fabersurfacecare.com)

#### 1.4. Emergency telephone number

For urgent inquiries refer to

**Belgium**  
Centre Antipoisons  
c/o Hôpital Militaire Reine Astrid, Rue Bruyn 1, 1120 Bruxelles, Belgium  
Phone+32022649636  
E-mail [info@poisoncentre.be](mailto:info@poisoncentre.be)

**Croatia**  
Croatian Institute of Public Health, Division for Toxicology  
Borongajska 83g, 10000 Zagreb, Croatia  
Phone+38514686910  
E-mail [toksikologija@hzjz.hr](mailto:toksikologija@hzjz.hr)

**Denmark**  
Danish Environmental Protection Agency  
Haraldsgade 53, 2100 København Ø, Denmark  
Phone+45 72 54 40 00  
E-mail [mst@mst.dk](mailto:mst@mst.dk)

**Estonia**  
Health Board  
Paldiski road 81,10617 Tallinn, Estonia  
Phone+372 794 3500  
E-mail [clp@terviseamet.ee](mailto:clp@terviseamet.ee), [info@terviseamet.ee](mailto:info@terviseamet.ee)

**Iceland**  
Poisons Information Center - Icelandic University Hospital  
Fossvogur, Reykjavík, Iceland  
Phone+354 543 22 22  
E-mail [eitur@landspitali.is](mailto:eitur@landspitali.is)

**Ireland**  
National Poisons Information Centre  
Beaumont Hospital, Beaumont, Dublin 9., Ireland  
E-mail [chemicalsinfo@beaumont.ie](mailto:chemicalsinfo@beaumont.ie)

**Latvia**



**FABER CHIMICA S.R.L.**  
**PPF12 - DEEP ENHANCER**

Revision n. 10.1  
Dated 04/03/2022  
Printed on 04/03/2022  
Page n. 2/16  
Replaced revision:10.0 (Dated: 13/10/2021)

State Ltd "Latvian Environment, Geology and Meteorology Centre"  
Maskavas Street 165, Riga, LV-1019, Latvia  
Phone +371 67032600  
E-mail lvgmc@lvgmc.lv  
Lithuania  
Environmental Protection Agency  
Juozapavicius st. 9, LT-09311 Vilnius, Lithuania  
Phone +370 70662008  
E-mail aaa@aaa.am.lt  
Malta  
Malta Competition and Consumer Affairs Authority (MCCAA)  
Mizzi House, National Road, Blata I-Bajda HMR9010, Malta  
Phone +356 2395 2000  
E-mail info@mccaa.org.mt  
Norway  
Norwegian Environment Agency  
Postboks 5672 Torgarden, 7485 Trondheim, Norway  
Phone+4573580500  
E-mail produktregisteret@miljodir.no  
Portugal  
Centro de informação antivenenos  
Rua Almirante Barroso, 36 1000-013 Lisboa, Portugal  
Phone +351213303271  
E-mail ciav.tox@inem.pt  
Sweden  
Swedish Poisons Information Centre  
Giftinformationscentralen 171 76 Stockholm, Sweden  
Phone +46104566750  
E-mail giftinformation@gic.se

## SECTION 2. Hazards identification

### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.  
Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 2	H225	Highly flammable liquid and vapour.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.

### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:

Danger



**FABER CHIMICA S.R.L.**  
**PPF12 - DEEP ENHANCER**

Revision n. 10.1  
Dated 04/03/2022  
Printed on 04/03/2022  
Page n. 3/16  
Replaced revision:10.0 (Dated: 13/10/2021)

Hazard statements:

**H225** Highly flammable liquid and vapour.  
**H304** May be fatal if swallowed and enters airways.  
**H336** May cause drowsiness or dizziness.  
**EUH066** Repeated exposure may cause skin dryness or cracking.

Precautionary statements:

**P210** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
**P331** Do NOT induce vomiting.  
**P301+P310** IF SWALLOWED: Immediately call a POISON CENTER / doctor  
**P370+P378** In case of fire: use carbon dioxide, foam, chemical powder to extinguish.  
**P403+P235** Store in a well-ventilated place. Keep cool.  
**P405** Store locked up.

**Contains:** Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics  
METHYL ACETATE

**2.3. Other hazards**

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration  $\geq$  0.1%.

## SECTION 3. Composition/information on ingredients

### 3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
<b>Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, &lt;2% aromatics</b> CAS 64742-48-9 EC 919-857-5 INDEX REACH Reg. 01-2119463258-33	$74 \leq x < 78$	Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066
<b>METHYL ACETATE</b> CAS 79-20-9 EC 201-185-2 INDEX 607-021-00-X	$8 \leq x < 9$	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066
<b>METHANOL</b> CAS 67-56-1 EC 200-659-6 INDEX 603-001-00-X	$1,5 \leq x < 2$	Flam. Liq. 2 H225, Acute Tox. 3 H301, Acute Tox. 3 H311, Acute Tox. 3 H331, STOT SE 1 H370 STOT SE 2 H371: $\geq 3\%$ STA Oral: 100 mg/kg, STA Dermal: 300 mg/kg, STA Inhalation mists/powders: 0,501 mg/l, STA Inhalation vapours: 3 mg/l

The full wording of hazard (H) phrases is given in section 16 of the sheet.



**FABER CHIMICA S.R.L.**  
**PPF12 - DEEP ENHANCER**

Revision n. 10.1  
Dated 04/03/2022  
Printed on 04/03/2022  
Page n. 4/16  
Replaced revision:10.0 (Dated: 13/10/2021)

## SECTION 4. First aid measures

### 4.1. Description of first aid measures

**EYES:** Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

**SKIN:** Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

**INHALATION:** Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

**INGESTION:** Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

## SECTION 5. Firefighting measures

### 5.1. Extinguishing media

#### SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

#### UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

### 5.2. Special hazards arising from the substance or mixture

#### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

### 5.3. Advice for firefighters

#### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

#### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## SECTION 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.



**FABER CHIMICA S.R.L.**  
**PPF12 - DEEP ENHANCER**

Revision n. 10.1  
Dated 04/03/2022  
Printed on 04/03/2022  
Page n. 5/16  
Replaced revision:10.0 (Dated: 13/10/2021)

## 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

## 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

## 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

# SECTION 7. Handling and storage

## 7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

## 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

## 7.3. Specific end use(s)

Information not available

# SECTION 8. Exposure controls/personal protection

## 8.1. Control parameters

Regulatory References:

DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
ESP	España	Límites de exposición profesional para agentes químicos en España 2021
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	TLV-ACGIH RCP TLV	ACGIH 2021 ACGIH TLVs and BEIs – Appendix H

## METHANOL

### Threshold Limit Value



**FABER CHIMICA S.R.L.**  
**PPF12 - DEEP ENHANCER**

Revision n. 10.1  
Dated 04/03/2022  
Printed on 04/03/2022  
Page n. 6/16  
Replaced revision:10.0 (Dated: 13/10/2021)

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	270	200	1080	800	SKIN
MAK	DEU	130	100	260	200	SKIN
VLA	ESP	266	200			SKIN
VLEP	FRA	260	200	1300	1000	SKIN 11
VLEP	ITA	260	200			SKIN
TGG	NLD	133				SKIN
WEL	GBR	266	200	333	250	SKIN
OEL	EU	260	200			
TLV-ACGIH		262	200	328	250	SKIN

**METHYL ACETATE**  
**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	620	200	1240 (C)	400 (C)	
MAK	DEU	310	100	1240	400	
VLA	ESP	616	200	770	250	
VLEP	FRA	610	200	760	250	SKIN
TGG	NLD	100				
WEL	GBR	616	200	770	250	
TLV-ACGIH		606	200	757	250	

**Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics**  
**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
RCP TLV		1200	197			

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

**8.2. Exposure controls**

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

**HAND PROTECTION**

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

**SKIN PROTECTION**



**FABER CHIMICA S.R.L.**  
**PPF12 - DEEP ENHANCER**

Revision n. 10.1  
Dated 04/03/2022  
Printed on 04/03/2022  
Page n. 7/16  
Replaced revision:10.0 (Dated: 13/10/2021)

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

#### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

#### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a type AX filter, whose limit of use will be defined by the manufacturer (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

#### ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

## SECTION 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	colourless	
Odour	characteristic of solvent	
Melting point / freezing point	Not available	
Initial boiling point	Not available	
Flammability	flammable liquid	
Lower explosive limit	Not available	
Upper explosive limit	Not available	
Flash point	< 21 °C	
Auto-ignition temperature	< 200 °C	
pH	Not available	Reason for missing data:substance/mixture is non-soluble (in water)
Kinematic viscosity	55	
Solubility	partially soluble in water	
Partition coefficient: n-octanol/water	2,3	Temperature: 25 °C
Vapour pressure	Not available	
Density and/or relative density	800-820 g/cm <sup>3</sup>	
Relative vapour density	Not available	
Particle characteristics	Not applicable	

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

Information not available



**FABER CHIMICA S.R.L.**  
**PPF12 - DEEP ENHANCER**

Revision n. 10.1  
Dated 04/03/2022  
Printed on 04/03/2022  
Page n. 8/16  
Replaced revision:10.0 (Dated: 13/10/2021)

9.2.2. Other safety characteristics

VOC (Directive 2010/75/EU) 100,00 % - 810,00  
g/litre

## SECTION 10. Stability and reactivity

### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

### 10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

### 10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

### 10.5. Incompatible materials

Information not available

### 10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

## SECTION 11. Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Metabolism, toxicokinetics, mechanism of action and other information

Information not available

#### Information on likely routes of exposure

#### METHANOL

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.





**FABER CHIMICA S.R.L.**  
**PPF12 - DEEP ENHANCER**

Revision n. 10.1  
Dated 04/03/2022  
Printed on 04/03/2022  
Page n. 9/16  
Replaced revision:10.0 (Dated: 13/10/2021)

Delayed and immediate effects as well as chronic effects from short and long-term exposure

**METHANOL**

The minimum lethal dose for humans by ingestion is considered to be in the range from 300 to 1000 mg/kg. Ingestion of 4-10 ml of the substance may cause permanent blindness in adult humans (IPCS).

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation - mists / powders) of the mixture:	> 5 mg/l
ATE (Inhalation - vapours) of the mixture:	> 20 mg/l
ATE (Inhalation - gas) of the mixture:	0,0 mg/l
ATE (Oral) of the mixture:	>2000 mg/kg
ATE (Dermal) of the mixture:	>2000 mg/kg

**METHANOL**

STA (Oral):	100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
STA (Dermal):	300 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
STA (Inhalation mists/powders):	0,501 mg/l estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
STA (Inhalation vapours):	3 mg/l estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

LD50 (Dermal):	> 5000 mg/kg rabbits
LD50 (Oral):	> 5000 mg/kg rat
LC50 (Inhalation vapours):	> 5000 mg/m3

SKIN CORROSION / IRRITATION

Repeated exposure may cause skin dryness or cracking.

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION



**FABER CHIMICA S.R.L.**  
**PPF12 - DEEP ENHANCER**

Revision n. 10.1  
Dated 04/03/2022  
Printed on 04/03/2022  
Page n. 10/16  
Replaced revision:10.0 (Dated: 13/10/2021)

Does not meet the classification criteria for this hazard class

Respiratory sensitization

Information not available

Skin sensitization

Information not available

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

Adverse effects on sexual function and fertility

Information not available

Adverse effects on development of the offspring

Information not available

Effects on or via lactation

Information not available



**FABER CHIMICA S.R.L.**  
**PPF12 - DEEP ENHANCER**

Revision n. 10.1  
Dated 04/03/2022  
Printed on 04/03/2022  
Page n. 11/16  
Replaced revision:10.0 (Dated: 13/10/2021)

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

Target organs

Information not available

Route of exposure

Information not available

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

Target organs

Information not available

Route of exposure

Information not available

ASPIRATION HAZARD

Toxic for aspiration

**11.2. Information on other hazards**

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

**SECTION 12. Ecological information**



**FABER CHIMICA S.R.L.**  
**PPF12 - DEEP ENHANCER**

Revision n. 10.1  
Dated 04/03/2022  
Printed on 04/03/2022  
Page n. 12/16  
Replaced revision:10.0 (Dated: 13/10/2021)

**12.1. Toxicity**

Hydrocarbons, C9-C11, n-alkanes,  
isoalkanes, cyclics, <2% aromatics  
EC50 - for Crustacea 1000 mg/l/48h

**12.2. Persistence and degradability**

METHANOL  
Solubility in water 1000 - 10000 mg/l  
Rapidly degradable

METHYL ACETATE  
Solubility in water 243500 mg/l  
Rapidly degradable

**12.3. Bioaccumulative potential**

METHANOL  
Partition coefficient: n-octanol/water -0,77  
BCF 0,2

METHYL ACETATE  
Partition coefficient: n-octanol/water 0,18

**12.4. Mobility in soil**

METHYL ACETATE  
Partition coefficient: soil/water 0,18

**12.5. Results of PBT and vPvB assessment**

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

**12.6. Endocrine disrupting properties**

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

**12.7. Other adverse effects**

Information not available

**SECTION 13. Disposal considerations**

**13.1. Waste treatment methods**



**FABER CHIMICA S.R.L.**  
**PPF12 - DEEP ENHANCER**

Revision n. 10.1  
Dated 04/03/2022  
Printed on 04/03/2022  
Page n. 13/16  
Replaced revision:10.0 (Dated: 13/10/2021)

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

**CONTAMINATED PACKAGING**

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## SECTION 14. Transport information

### 14.1. UN number or ID number

ADR / RID, IMDG, 1263  
IATA:

### 14.2. UN proper shipping name

ADR / RID: PAINT or PAINT RELATED MATERIAL  
IMDG: PAINT or PAINT RELATED MATERIAL  
IATA: PAINT or PAINT RELATED MATERIAL

### 14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3  
IMDG: Class: 3 Label: 3  
IATA: Class: 3 Label: 3



### 14.4. Packing group

ADR / RID, IMDG, II  
IATA:

### 14.5. Environmental hazards

ADR / RID: NO  
IMDG: NO  
IATA: NO

### 14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 33	Limited Quantities: 5 L	Tunnel restriction code: (D/E)
IMDG:	Special provision: 163, 367, 640D, 650 EMS: F-E, <u>S-E</u>	Limited Quantities: 5 L	



**FABER CHIMICA S.R.L.**  
**PPF12 - DEEP ENHANCER**

Revision n. 10.1  
Dated 04/03/2022  
Printed on 04/03/2022  
Page n. 14/16  
Replaced revision:10.0 (Dated: 13/10/2021)

IATA:	Cargo:	Maximum quantity: 60 L	Packaging instructions: 364
	Pass.:	Maximum quantity: 5 L	Packaging instructions: 353
	Special provision:	A3, A72, A192	

**14.7. Maritime transport in bulk according to IMO instruments**

Information not relevant

**SECTION 15. Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EU: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product  
Point 3 - 40

Contained substance

Point 69 METHANOL

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

Not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage  $\geq$  than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls



**FABER CHIMICA S.R.L.**  
**PPF12 - DEEP ENHANCER**

Revision n. 10.1  
Dated 04/03/2022  
Printed on 04/03/2022  
Page n. 15/16  
Replaced revision:10.0 (Dated: 13/10/2021)

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

### 15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

## SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Flam. Liq. 2</b>	Flammable liquid, category 2
<b>Acute Tox. 3</b>	Acute toxicity, category 3
<b>STOT SE 1</b>	Specific target organ toxicity - single exposure, category 1
<b>Asp. Tox. 1</b>	Aspiration hazard, category 1
<b>Eye Irrit. 2</b>	Eye irritation, category 2
<b>STOT SE 3</b>	Specific target organ toxicity - single exposure, category 3
<b>H225</b>	Highly flammable liquid and vapour.
<b>H301</b>	Toxic if swallowed.
<b>H311</b>	Toxic in contact with skin.
<b>H331</b>	Toxic if inhaled.
<b>H370</b>	Causes damage to organs.
<b>H304</b>	May be fatal if swallowed and enters airways.
<b>H319</b>	Causes serious eye irritation.
<b>H336</b>	May cause drowsiness or dizziness.
<b>EUH066</b>	Repeated exposure may cause skin dryness or cracking.

### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.



**FABER CHIMICA S.R.L.**  
**PPF12 - DEEP ENHANCER**

Revision n. 10.1  
Dated 04/03/2022  
Printed on 04/03/2022  
Page n. 16/16  
Replaced revision:10.0 (Dated: 13/10/2021)

- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

**GENERAL BIBLIOGRAPHY**

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
  2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
  3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
  4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
  5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
  6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
  7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
  8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
  9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
  10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
  11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
  12. Regulation (EU) 2016/1179 (IX Atp. CLP)
  13. Regulation (EU) 2017/776 (X Atp. CLP)
  14. Regulation (EU) 2018/669 (XI Atp. CLP)
  15. Regulation (EU) 2019/521 (XII Atp. CLP)
  16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
  17. Regulation (EU) 2019/1148
  18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
  19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
  20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
  21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- The Merck Index. - 10th Edition
  - Handling Chemical Safety
  - INRS - Fiche Toxicologique (toxicological sheet)
  - Patty - Industrial Hygiene and Toxicology
  - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
  - IFA GESTIS website
  - ECHA website
  - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

**CALCULATION METHODS FOR CLASSIFICATION**

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

**Changes to previous review:**

The following sections were modified:

02 / 03 / 11 / 12 / 14 / 15.