



**FABER CHIMICA S.R.L.**  
**PPF53 - EPOXY RESIDUE REMOVER**

Revision n. 2.1  
Dated 27/10/2021  
Printed on 27/10/2021  
Page n. 1/14  
Replaced revision:2.0 (Dated: 17/12/2019)

## Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Code: PFP53  
Product name: EPOXY RESIDUE REMOVER  
Chemical name and synonym: EPOXY RESIDUE REMOVER  
UFI: S6G0-H0NA-Y00W-RC9D

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: ALKALINE DETERGENT FOR THE REMOVAL OF EPOXY GROUT

#### 1.3. Details of the supplier of the safety data sheet

Name: FABER CHIMICA S.R.L.  
Full address: Via Ceresani 10  
District and Country: 60044 Campo D'Olmo - Fabriano (ANCONA)  
ITALIA  
Tel. 0732627178  
Fax 073222395

e-mail address of the competent person responsible for the Safety Data Sheet: [quality@fabersurfacecare.com](mailto:quality@fabersurfacecare.com)

#### 1.4. Emergency telephone number

For urgent inquiries refer to

**Belgium**  
Centre Antipoisons  
c/o Hôpital Militaire Reine Astrid, Rue Bruyn 1, 1120 Bruxelles, Belgium  
Phone+32022649636  
E-mail [info@poisoncentre.be](mailto:info@poisoncentre.be)

**Croatia**  
Croatian Institute of Public Health, Division for Toxicology  
Borongajska 83g, 10000 Zagreb, Croatia  
Phone+38514686910  
E-mail [toksikologija@hzjz.hr](mailto:toksikologija@hzjz.hr)

**Denmark**  
Danish Environmental Protection Agency  
Haraldsgade 53, 2100 København Ø, Denmark  
Phone+45 72 54 40 00  
E-mail [mst@mst.dk](mailto:mst@mst.dk)

**Estonia**  
Health Board  
Paldiski road 81,10617 Tallinn, Estonia  
Phone+372 794 3500  
E-mail [clp@terviseamet.ee](mailto:clp@terviseamet.ee), [info@terviseamet.ee](mailto:info@terviseamet.ee)

**Iceland**  
Poisons Information Center - Icelandic University Hospital  
Fossvogur, Reykjavik, Iceland  
Phone+354 543 22 22  
E-mail [eitur@landspitali.is](mailto:eitur@landspitali.is)

**Ireland**  
National Poisons Information Centre  
Beaumont Hospital, Beaumont, Dublin 9., Ireland  
E-mail [chemicalsinfo@beaumont.ie](mailto:chemicalsinfo@beaumont.ie)



**FABER CHIMICA S.R.L.**  
**PFP53 - EPOXY RESIDUE REMOVER**

Revision n. 2.1  
Dated 27/10/2021  
Printed on 27/10/2021  
Page n. 2/14  
Replaced revision:2.0 (Dated: 17/12/2019)

**Latvia**  
State Ltd "Latvian Environment, Geology and Meteorology Centre"  
Maskavas Street 165, Riga, LV-1019, Latvia  
Phone +371 67032600  
E-mail lvgmc@lvgmc.lv

**Lithuania**  
Environmental Protection Agency  
Juozapavicius st. 9, LT-09311 Vilnius, Lithuania  
Phone +370 70662008  
E-mail aaa@aaa.am.lt

**Malta**  
Malta Competition and Consumer Affairs Authority (MCCAA)  
Mizzi House, National Road, Blata I-Bajda HMR9010, Malta  
Phone +356 2395 2000  
E-mail info@mccaa.org.mt

**Norway**  
Norwegian Environment Agency  
Postboks 5672 Torgarden, 7485 Trondheim, Norway  
Phone+4573580500  
E-mail produktregisteret@miljodir.no

**Portugal**  
Centro de informação antivenenos  
Rua Almirante Barroso, 36 1000-013 Lisboa, Portugal  
Phone +351213303271  
E-mail ciav.tox@inem.pt

**Sweden**  
Swedish Poisons Information Centre  
Giftinformationscentralen 171 76 Stockholm, Sweden  
Phone +46104566750  
E-mail giftinformation@gic.se

## SECTION 2. Hazards identification

### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Skin corrosion, category 1

H314

Causes severe skin burns and eye damage.

Serious eye damage, category 1

H318

Causes serious eye damage.

### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:

Danger



FABER CHIMICA S.R.L.  
PFP53 - EPOXY RESIDUE REMOVER

Revision n. 2.1  
Dated 27/10/2021  
Printed on 27/10/2021  
Page n. 3/14  
Replaced revision:2.0 (Dated: 17/12/2019)

Hazard statements:

**H314** Causes severe skin burns and eye damage.

Precautionary statements:

**P260** Do not breathe dust / fume / gas / mist / vapours / spray.  
**P305+P351+P338** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
**P303+P361+P353** IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
**P280** Wear protective gloves/ protective clothing / eye protection / face protection.  
**P310** Immediately call a POISON CENTER / doctor  
**P264** Wash hands and face thoroughly after handling.

**Contains:** alcohols, C11-15-secondary, ethoxylated  
Sodium silicate

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration  $\geq$  0.1%.

## SECTION 3. Composition/information on ingredients

### 3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
<b>Sodium silicate</b>		
CAS 1344-09-8	$35 \leq x < 37,5$	Eye Irrit. 2 H319, Skin Irrit. 2 H315
EC 215-687-4		
INDEX -		
REACH Reg. 01-2119448725-31		
<b>alcohols, C11-15-secondary, ethoxylated</b>		
CAS 68131-40-8	$2,5 \leq x < 3$	Acute Tox. 4 H302, Eye Dam. 1 H318, Aquatic Chronic 3 H412
EC		STA Oral: 500 mg/kg
INDEX -		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

## SECTION 4. First aid measures

### 4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.



**FABER CHIMICA S.R.L.**  
**PPF53 - EPOXY RESIDUE REMOVER**

Revision n. 2.1  
Dated 27/10/2021  
Printed on 27/10/2021  
Page n. 4/14  
Replaced revision:2.0 (Dated: 17/12/2019)

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Wash contaminated clothing before using it again.  
INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.  
INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

## SECTION 5. Firefighting measures

### 5.1. Extinguishing media

#### SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

#### UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

### 5.2. Special hazards arising from the substance or mixture

#### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

### 5.3. Advice for firefighters

#### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

#### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## SECTION 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.



FABER CHIMICA S.R.L.  
PFP53 - EPOXY RESIDUE REMOVER

Revision n. 2.1  
Dated 27/10/2021  
Printed on 27/10/2021  
Page n. 5/14  
Replaced revision:2.0 (Dated: 17/12/2019)

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

## SECTION 7. Handling and storage

#### 7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

#### 7.3. Specific end use(s)

Information not available

## SECTION 8. Exposure controls/personal protection

#### 8.1. Control parameters

Regulatory References:

TLV-ACGIH

ACGIH 2020

#### Sodium silicate

##### Threshold Limit Value

Type	Country	TWA/8h	STEL/15min	Remarks / Observations
		mg/m3	ppm	
			mg/m3	ppm
TLV-ACGIH		2		
Predicted no-effect concentration - PNEC				
Normal value in fresh water			7,5	mg/l
Normal value in marine water			1	mg/l
Normal value for water, intermittent release			7,5	mg/l
Normal value of STP microorganisms			348	mg/l

##### Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				0,8 mg/kg/d				
Inhalation				1,38 mg/m3				5,61 mg/m3
Skin				0,8 mg/kg/d				1,59 mg/kg/d

Legend:



**FABER CHIMICA S.R.L.**  
**PPF53 - EPOXY RESIDUE REMOVER**

Revision n. 2.1  
Dated 27/10/2021  
Printed on 27/10/2021  
Page n. 6/14  
Replaced revision:2.0 (Dated: 17/12/2019)

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

## 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

### SKIN PROTECTION

Wear category III professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

### EYE PROTECTION

Wear a hood visor or protective visor combined with airtight goggles (see standard EN 166).

### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

### ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

## SECTION 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	viscous liquid	
Colour	white	
Odour	characteristic	
Odour threshold	Not determined	
Melting point / freezing point	< 30 °C	
Initial boiling point	> 96 °C	
Flammability	not flammable	
Lower explosive limit	Not available	
Upper explosive limit	Not available	



**FABER CHIMICA S.R.L.**  
**PPF53 - EPOXY RESIDUE REMOVER**

Revision n. 2.1  
Dated 27/10/2021  
Printed on 27/10/2021  
Page n. 7/14  
Replaced revision:2.0 (Dated: 17/12/2019)

Flash point	Not applicable
Auto-ignition temperature	Not available
Decomposition temperature	Not available
pH	12
Kinematic viscosity	1000
Solubility	soluble in water
Partition coefficient: n-octanol/water	Not applicable
Vapour pressure	2338,54 Pa
Density and/or relative density	1110-1130
Relative vapour density	Not available
Particle characteristics	Not applicable

## 9.2. Other information

9.2.1. Information with regard to physical hazard classes  
Information not available

9.2.2. Other safety characteristics

Information not available

## SECTION 10. Stability and reactivity

### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

Sodium silicate

May react with: aluminium,zinc,tin

### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

Sodium silicate

Stable in normal conditions of use and storage

### 10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

Sodium silicate

May react violently with: strong acids

### 10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.



**FABER CHIMICA S.R.L.**  
**PFP53 - EPOXY RESIDUE REMOVER**

Revision n. 2.1  
Dated 27/10/2021  
Printed on 27/10/2021  
Page n. 8/14  
Replaced revision:2.0 (Dated: 17/12/2019)

#### 10.5. Incompatible materials

Sodium silicate

Keep away from: acids

#### 10.6. Hazardous decomposition products

Sodium silicate

May develop: carbon oxides

## SECTION 11. Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Metabolism, toxicokinetics, mechanism of action and other information

Information not available

##### Information on likely routes of exposure

Information not available

##### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

##### Interactive effects

Information not available

##### ACUTE TOXICITY

ATE (Inhalation) of the mixture:	Not classified (no significant component)
ATE (Oral) of the mixture:	>2000 mg/kg
ATE (Dermal) of the mixture:	Not classified (no significant component)

alcohols, C11-15-secondary, ethoxylated

LD50 (Oral):	> 2380 mg/kg Rat
--------------	------------------





**FABER CHIMICA S.R.L.**  
**PPF53 - EPOXY RESIDUE REMOVER**

Revision n. 2.1  
Dated 27/10/2021  
Printed on 27/10/2021  
Page n. 9/14  
Replaced revision:2.0 (Dated: 17/12/2019)

STA (Oral): 500 mg/kg estimate from table 3.1.2 of Annex I of the CLP  
(figure used for calculation of the acute toxicity estimate of the mixture)

LD50 (Dermal): > 1124 mg/kg bw Rabbit

Sodium silicate

LD50 (Oral): 3400 mg/kg rat  
LD50 (Dermal): > 5000 mg/kg rat

SKIN CORROSION / IRRITATION

Corrosive for the skin

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class



**FABER CHIMICA S.R.L.**  
**PFP53 - EPOXY RESIDUE REMOVER**

Revision n. 2.1  
Dated 27/10/2021  
Printed on 27/10/2021  
Page n. 10/14  
Replaced revision:2.0 (Dated: 17/12/2019)

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

**11.2. Information on other hazards**

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

**SECTION 12. Ecological information**

**12.1. Toxicity**

alcohols, C11-15-secondary, ethoxylated

EC50 - for Algae / Aquatic Plants > 52 mg/l/72h Selenastrum sp

Sodium silicate

LC50 - for Fish 1108 mg/l/96h Brachydanio rerio

EC50 - for Algae / Aquatic Plants > 345,4 mg/l/72h Scenedesmus subspicatus

**12.2. Persistence and degradability**

Sodium silicate

Rapidly degradable

**12.3. Bioaccumulative potential**

alcohols, C11-15-secondary, ethoxylated

Partition coefficient: n-octanol/water 5,082 QSAR

**12.4. Mobility in soil**

alcohols, C11-15-secondary, ethoxylated

Partition coefficient: soil/water 4,446 QSAR

**12.5. Results of PBT and vPvB assessment**

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

**12.6. Endocrine disrupting properties**



**FABER CHIMICA S.R.L.**  
**PFP53 - EPOXY RESIDUE REMOVER**

Revision n. 2.1  
Dated 27/10/2021  
Printed on 27/10/2021  
Page n. 11/14  
Replaced revision:2.0 (Dated: 17/12/2019)

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

**12.7. Other adverse effects**

Information not available

## SECTION 13. Disposal considerations

### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

**CONTAMINATED PACKAGING**

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

### 14.1. UN number or ID number

Not applicable

### 14.2. UN proper shipping name

Not applicable

### 14.3. Transport hazard class(es)

Not applicable

### 14.4. Packing group

Not applicable

### 14.5. Environmental hazards



**FABER CHIMICA S.R.L.**  
**PFP53 - EPOXY RESIDUE REMOVER**

Revision n. 2.1  
Dated 27/10/2021  
Printed on 27/10/2021  
Page n. 12/14  
Replaced revision:2.0 (Dated: 17/12/2019)

Not applicable

**14.6. Special precautions for user**

Not applicable

**14.7. Maritime transport in bulk according to IMO instruments**

Information not relevant

**SECTION 15. Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EC: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product  
Point 3

Regulation (EC) No. 2019/1148 - on the marketing and use of explosives precursors

Not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage  $\geq$  than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls



**FABER CHIMICA S.R.L.**  
**PPF53 - EPOXY RESIDUE REMOVER**

Revision n. 2.1  
Dated 27/10/2021  
Printed on 27/10/2021  
Page n. 13/14  
Replaced revision:2.0 (Dated: 17/12/2019)

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

### 15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

## SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Acute Tox. 4</b>	Acute toxicity, category 4
<b>Skin Corr. 1</b>	Skin corrosion, category 1
<b>Eye Dam. 1</b>	Serious eye damage, category 1
<b>Eye Irrit. 2</b>	Eye irritation, category 2
<b>Skin Irrit. 2</b>	Skin irritation, category 2
<b>Aquatic Chronic 3</b>	Hazardous to the aquatic environment, chronic toxicity, category 3
<b>H302</b>	Harmful if swallowed.
<b>H314</b>	Causes severe skin burns and eye damage.
<b>H318</b>	Causes serious eye damage.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H412</b>	Harmful to aquatic life with long lasting effects.

### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).



**FABER CHIMICA S.R.L.**  
**PPF53 - EPOXY RESIDUE REMOVER**

Revision n. 2.1  
Dated 27/10/2021  
Printed on 27/10/2021  
Page n. 14/14  
Replaced revision:2.0 (Dated: 17/12/2019)

**GENERAL BIBLIOGRAPHY**

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
  2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
  3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
  4. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
  5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
  6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
  7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
  8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
  9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
  10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
  11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
  12. Regulation (EU) 2016/1179 (IX Atp. CLP)
  13. Regulation (EU) 2017/776 (X Atp. CLP)
  14. Regulation (EU) 2018/669 (XI Atp. CLP)
  15. Regulation (EU) 2019/521 (XII Atp. CLP)
  16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
  17. Regulation (EU) 2019/1148
  18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
  19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
  20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
  21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- The Merck Index. - 10th Edition
  - Handling Chemical Safety
  - INRS - Fiche Toxicologique (toxicological sheet)
  - Patty - Industrial Hygiene and Toxicology
  - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
  - IFA GESTIS website
  - ECHA website
  - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

**CALCULATION METHODS FOR CLASSIFICATION**

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

**Changes to previous review:**

MSDS update for software use